

**Technical Specifications:**

|              |  |                         |
|--------------|--|-------------------------|
| <b>Model</b> | <b>H2000</b>                               |                         |
| Capacity     | 2000VA                                     |                         |
| Input        | Nominal Voltage                            | 120Vac / 220Vac         |
|              | Nominal Voltage Acceptable Voltage         | 65-140Vac / 135-280Vac  |
|              | Range                                      | 65-140Vac / 135-280Vac  |
|              | Frequency                                  | 60Hz / 50Hz             |
| Output       | Voltage                                    | 120Vac / 220Vac         |
|              | Voltage Regulation (Battery Mode)          | 120Vac / 220Vac +/-3%   |
|              | Frequency Regulation (Battery Mode)        | +/-0.1Hz                |
|              | Power Factor                               | 0.7                     |
|              | Waveform                                   | Pure sine wave          |
| Battery      | Battery Voltage                            | 24Vdc                   |
|              | Battery Time (at full load)                | Long time available     |
|              | Max. Charging Current (4 Steps selectable) | 10-50 Amp               |
| Environment  | Relative Humidity                          | 0-95% non-condensing    |
|              | Operation Temperature                      | 0-40degree              |
|              | Audible Noise                              | Less than 50dBA (at 1M) |