

Long 12V 26AH Rechargeable Sealed Lead Acid Battery

Nominal Voltage (V)	12V	
Nominal Capacity	20 hour rate	(1.3A to 10.50V) 26Ah
	10 hour rate	(2.47A to 10.50V) 24.7Ah
	5 hour rate	(4.42A to 10.20V) 22.1Ah
	1 C	(26A to 9.60V) 13.87Ah
	3 C	(78A to 9.60V) 9.10Ah
Weight	Approx. 8.0kg(17.6Lbs.)	
Dimensions	Length (L)	
	Width (W)	
	Height (H)	
	Overall Height (HT)	
Internal Resistance (at 1KHz)	Approx. 11 mΩ	
Maximum Discharge Current for	5 seconds: 390A	
Charging Methods at 25°C(77°F)	Cycle use: Charging Voltage Coefficient -5.0mV/°C/cell	14.4 to 15.0V
	Maximum Charging Current :	7.8A
	Standby use: Float Charging Voltage Coefficient -3.0mV/°C/cell	13.5 to 13.8V
Operating Temperature Range	Charge	-15°C(5°F) to 40°C(104°F)
	Discharge	-15°C(5°F) to 50°C(122°F)
	Storage	-15°C(5°F) to 40°C(104°F)
Charge Retention (shelf life) at 20°C(68°F)	1 month	92%
	3 month	90%
	6 month	80%
Case Material	ABS UL94 HB Option: Flammability resistance of (UL94 V-0)	
Design Life	3-5 Years.	
Terminal	F8	