

ViewSonic CDE6520 65" Interactive Flat Panel

Display	Panel Size	65"
	Type/ Tech	TFT LCD Module. IPS type, DLED backlight
	Display Area (mm)	1428.48(H) x 803.52(V) (65" diagonal)
	Native Resolution	3840 x 2160
	Aspect Ratio	16:9
	Colors	1.07G colors
	Brightness	450 nits (typ.)
	Contrast Ratio	1200:1 Typ.
	Response Time	8 ms
	Viewing Angles	H = 178, V = 178 typ.
	Backlight Life:	50,000 Hours
	Operation Rating	24/7
	Surface Treatment	Anti-glare, 3H hardness, Haze 25%
	Bezel	Slim
	Orientation	Landscape
INPUT	HDMI	x2
	RGB / VGA	x1
	DisplayPort	x1
	Audio	x1 (3.5mm)
	RS-232	x1
	OPS Slot	x1 (Optional Intel OPS VPC12-WPO)
	WiFi Slot	x1 (Optional WiFi module LB-WIFI-001)
OUTPUT	Audio	x1 (3.5mm)
	SPDIF	x1 (Fiber)
LAN	RJ45	x1
USB	Type A	2.0 Type A: x 2 (USB Playback)3.0 Type A: x 1 (USB Playback)
SPEAKERS	Max. 16Wx2	
COMPATIBILITY	RGB PC/HDMI PC	Up to 1920x1080@60Hz. Refer to timing table
	HDMI	480i, 480p,720p,1080i,1080p, 4K2K@60Hz
	DisplayPort	480i, 480p,720p,1080i,1080p, 4K2K@60Hz
	Android Version	Android 8.0
POWER	Voltage	100V-240V,50/60Hz (AC)
	Consumption	Normal 220 W, Max 300 W
ERGONOMICS	Wall Mount (VESA®)	400x200 mm
OPERATING CONDITIONS	Temperature (° C)	0 to 40°C
	Humidity	20% ~ 80% non-condensing
DIMENSIONS (W x H x D)	Physical (inch / mm)	57.11 x 32.60 x 3.09 in/ 1450.6 x 828.1 x 78.5 mm
	Packaging (inch / mm)	63.19 x 37.99 x 8.66 in/1605 x 965 x 220 mm
WEIGHT	Net (lb / kg)	22.95 kg / 50.59 lbs (w/o stand)
	Gross (lb / kg)	33.6 kg/74.07 lbs
REGULATIONS	cULus, FCC, Energy Star, EPEAT, MX-CoC, Mexico Energy, CE, CB, RoHS, ErP, REACH, WEEE, Custom Union, UkrSEPRO, RCM, MEPS	

PACKAGE CONTENTS	1. CDE6520 commercial display 2. Remote control with batteries 3. Quick start guide 4. Power cables (1.5M) 5. HDMI cables x2 (1.5M/3M) 6. Wall mount screw 7. RS232 adapter
---------------------	---