

ViewSonic PG603X Projector

Native Resolution	1024x768
DC Type	DC3
Brightness	3500
Contrast Ratio with SuperEco Mode	22000:1
Display Color	1.07 Billion Colors
Light Source	Lamp
Light Source Life	5000/15000
Lamp Watt	190W
Lens	F=2.5-2.7, f=22.08-24.28mm
Projection Offset	125%+/-5%
Throw Ratio	1.97-2.17
Image Size	30" - 300"
Throw Distance	1.16m-13.42m (100" @ 3.97m)
Keystone	+/- 40° (Vertical)
Optical Zoom	1.1x
Audible Noise (Normal/Eco)	30dB
Response Time	16ms
Resolution Support	VGA (640 x 480) to FullHD (1920 x 1080)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120Hz
Input	
Computer in (share with component)	1
Composite	1
Audio-in (3.5mm)	1
HDMI (HDCP)	1 (HDMI 1.4/ HDCP 1.4)
Output	
Audio out (3.5mm)	1
Speaker	2W
USB Type A (Power)	1 (5V/ 1A)
Control	
RS232	1
USB Type Mini B (Services)	1
Others	
Power Supply Voltage	100-240V+/- 10%, 50/60Hz AC
Power Consumption	Normal: 240WStandby: <0.5W

Operating Temperature	0~40°C
Net Weight	2.1kg
Dimensions (WxDxH) with Adjustment Foot	320x210x123mm
Language	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
Standard Accessory	
Power Cord	1
VGA Cable	1
Remote Control	1
QSG	1
Optional Accessory	
Lamp/Light Source	RLC-111
Carry Bag	PJ-CASE-008