

ViewSonic PX748 4K Projector

Native Resolution	3840x2160
DMD Type	DC3
Brightness	4000 (ANSI Lumens)
Contrast Ratio with SuperEco Mode	12000:1
Display Color	1.07 Billion Colors
Light Source Type	Lamp
Light Source Life (hours) with Normal Mode	4000
Light Source Life (hours) with SuperEco Mode	20000
Lamp Watt	240W
Lens	F=1.94-2.12, f=12-15.6mm
Projection Offset	120%+/-6%
Throw Ratio	1.13-1.47
Optical Zoom	1.3x
Digital Zoom	0.8x-2.0x
Image Size	30"-300"
Throw Distance	0.75m~9.76m(100"@2.50m)
Keystone	H: +/-40°, V: +/-40°
Lens Shift V. Range	Up to 20% (Digital)
Lens Shift H. Range	Up to 20% (Digital)
Audible Noise (Normal)	33dB
Audible Noise (Eco)	28dB
Input Lag	4.2ms
Resolution Support	VGA (640 x 480) to 4K (3840 x 2160)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P
Horizontal Frequency	15K-135KHz
Vertical Scan Rate	23-240Hz
Input	
HDMI	2 (HDMI 2.0b, HDCP 1.4/2.2)
USB Type C	1 (5V/ 2A)
Output	
Audio-out (3.5mm)	1
Speaker	10W
USB Type A (Power)	1 (5V/ 1.5A)
12V Trigger (3.5mm)	1
Control	

RS232 (DB 9-pin male)	1
RJ45 (LAN control)	1
Others	
Power Supply Voltage	100-240V+/- 10%, 50/60Hz(AC in)
Power Consumption	Normal: 310WStandby: <0.5W
Operating Temperature	0~40°C
Net Weight	2.8kg
Dimensions (WxDxH) with Adjustment Foot	312x222x108mm
OSD Language	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages
Standard Accessory	
Power Cord	1
USB-C Cable	1
Remote Control	1(w/ backlit)
QSG	Yes
Optional Accessory	
Lamp/Light Source	RLC-127
Carry Bag	PJ-CASE-008